



CB STYLE	LENGTH	WIDTH	DEPTH
TYPE 1 CB	24"	20"	VARIABLE
TYPE 1 CCI	29.5"	24"	VARIABLE
USA G2	32.5"	27.5"	VARIABLE

INLET SEDIMENT CONTROL DEVICE – SILT SACK

NOTES:

1. THE DIMENSION CHART ABOVE IS FOR STANDARD CATCH BASINS AND INLETS ONLY. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING THE CORRECT SIZE DEVICE FOR EACH INLET.
2. FOR NON-STANDARD CATCH BASINS AND INLETS, THE CONTRACTOR SHALL MEASURE DIMENSIONS IN THE FIELD AND ORDER THE APPROPRIATE SIZE(S).
3. THE INLET SEDIMENT CONTROL DEVICE SHALL BE OF HIGH FLOW DESIGN (200 GAL/MIN/FT), AS PER THE MANUFACTURER'S SPECS.
4. THE SEDIMENT CONTROL DEVICE SHALL BE INSPECTED DAILY BY THE CONTRACTOR AND MAINTAINED A MINIMUM ONCE PER MONTH OR WITHIN THE 48 HOURS FOLLOWING A STORM EVENT. FILTER SHALL BE CLEANED IN A MANNER WHICH ENSURES THAT ALL SEDIMENT REMAINS ON SITE.
5. SUBSTITUTION OF A SHEET OF FILTER FABRIC PLACED OVER THE OPENING OF THE INLET IS NOT APPROVED.
6. RECESSED CURB INLET CATCH BASINS MUST BE BLOCKED WHEN USING FILTER FABRIC INLET SACKS, SIZE OF FILTER INLET SACK TO BE DETERMINED BY MANUFACTURER.
7. THE FILTER SHALL BE REPLACED OR CLEANED WHEN THE BAG BECOMES HALF FULL.
8. SEE INLET PROTECTION NOTES STD. DETAIL E3.

NO.	REVISIONS	DATE	BY

DWG: E3d.DWG



Department of
 Public Works
CLARK COUNTY
 WASHINGTON
 proud past, promising future

INLET PROTECTION TYPE 5
 SILT SACK
 APPROVED
Peter Capen
 COUNTY ENGINEER
 5/23/08
 DATE

STANDARD
E3d
 DETAIL
 DESIGNED
 DRAWN
 DATE 05/23/08