



CONVENTIONAL CONSTRUCTION		
AASHTO SOIL TYPE	BASE ROCK	SUBBASE ROCK THICKNESS
A-1	0.35'	0.00'
A-2	0.35'	0.00'
A-3	0.42'	0.00'
A-4	0.50'	0.00'
A-5	0.50'	0.55'
A-6	0.50'	0.67'
A-7	0.50'	0.80'

NOTES:

1. SUBGRADE REINFORCEMENT GEOTEXTILES (OR EQUIVALENT) SHALL BE INSTALLED OVER ALL A-6, A-7 SOILS PRIOR TO CONSTRUCTING THE BASE AND SURFACING.
2. THE SUBGRADE AND CRUSHED SURFACING MATERIALS SHALL BE COMPACTED PER WSDOT STANDARDS.
3. FEATURES WITHIN CORE ROAD AND FLEX ZONE ARE SUBJECT TO CCC 40.350.030(B)(3) AND TABLE CCC 40.350.030-2.
4. STORMWATER LOW IMPACT DEVELOPMENT (LID) FEATURES IN THE RIGHT-OF-WAY ARE SUBJECT TO CCC 40.350.030(B)(3) AND TABLE CCC 40.350.030-2.



Department of  
Public Works  
**CLARK COUNTY**  
WASHINGTON  
proud part, promising future

RURAL PRIVATE ROAD

*Peter Capen*  
COUNTY ENGINEER

APPROVED

09/18/13  
DATE

DRAWING  
22

DESIGNED  
DRAWN  
DATE 09/18/13