

SIGN INSTALL SPECIFICATIONS


POST NUMBER	SHEET	STATION	OFFSET	SIGN CODE	SIGN DESCRIPTION	SIGN SIZE (IN)		AREA (SF)	SIGN SHEETING TYPE	POST MATERIAL	POST SIZE (TRADE SIZE)	NUMBER OF POSTS	POST HT ABOVE GRADE (FT)	BASE TYPE	REMARKS
						X	Y								
201	SS9	133+52	63-FT RT	R10-6L	STOP HERE ON RED	24	36	6	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	10	ST4	FACING EB RT TURN LANE TRAFFIC
202	SS1	22+90	50-FT RT	R10-6L	STOP HERE ON RED	24	36	6	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	10	ST4	FACING NB TRAFFIC
203	SS1			R9-6	BIKES YIELD TO PEDS	12	18	1.5	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	9.5	ST4	SIGN ON TRAIL FACING WEST- BOTT. OF SIGN 8 FT. ABOVE SURFACE.
204	SS9	136+40	60-FT RT	W9-1R	RIGHT LANE ENDS	36	36	9	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	11.5	ST4	FACING EB TRAFFIC
205	SS9	138+20	56-FT RT	W4-2	RIGHT LANE ENDS (SYMBOL)	36	36	9	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	11.5	ST4	FACING EB TRAFFIC
206	SS9	140+42	51-FT LT	R3-7R	RIGHT LANE MUST TURN RIGHT	30	30	6.25	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	9.5	ST4	FACING EB TRAFFIC
207	SS9	136+50	51-FT LT	R3-7R	RIGHT LANE MUST TURN RIGHT	30	30	6.25	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	9.5	ST4	FACING WB TRAFFIC
208	SS9	135+27	71-FT LT	R10-6L	STOP HERE ON RED	24	36	6	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	10	ST4	FACING WB RT TURN TRAFFIC
209	SSI	25+00	52-FT LT	R10-6L	STOP HERE ON RED	24	36	6	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	10	ST4	FACING SB TRAFFIC
210	SS9	132+35	51-FT LT	W9-1R	RIGHT LANE ENDS	36	36	9	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	11.5	ST4	FACING SB RT TURN LANE TRAFFIC
211	SS8	130+40	51-FT LT	W4-2	RIGHT LANE ENDS (SYMBOL)	36	36	9	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	11.5	ST4	FACING WB TRAFFIC
212	SS6	23+00	68-FT LT	R9-6	BIKES YIELD TO PEDS	12	18	1.5	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	9.5	ST4	FACING EB RT TURN TRAFFIC. BOTT. OF SIGN 8 FT. ABOVE SURFACE.
213	SS1	21+55	41-FT LT	CUSTOM	BIKES MUST USE SIDEWALK	24	24	4	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	10	ST4	FACING SB TRAFFIC. BOTT. OF SIGN 8 FT. ABOVE SURFACE
214	SS1	16+80	42-FT RT	D3-2	PADDEN PKWY NEXT SIGNAL	30	21	4.375	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	13	ST4	FACING NB TRAFFIC
				W4-7	THRU TRAFFIC MERGE LEFT	36	36	9							FACING NB TRAFFIC
215	SS1	18+30	40-FT RT	R7-102	BIKE LANE	24	30	5	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	10.5	ST4	FACING NB TRAFFIC
				R3-17b	ENDS 300 FT	30	12	2.5							FACING NB TRAFFIC
216	SS1	21+36	40-FT RT	R9-6	BIKES YIELD TO PEDS	12	18	1.5	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	11	ST4	FACING SB TRAFFIC
				CUSTOM	BIKES USE SIDEWALK	18	18	2.25							FACING SB TRAFFIC, LETTER SIZE 3C, MOUNTED ABOVE YIELD
217	SS1	25+05	61-FT RT	R9-7	BIKES KEEP RIGHT (SYMBOL)	12	18	1.5	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	9.5	ST4	FACING NB. BOTTOM OF SIGN 8 FT. ABOVE SURFACE
218	SS1	27+85	33-FT RT	R9-7	BIKES KEEP RIGHT (SYMBOL)	12	18	1.5	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	11	ST4	FACING NB TRAFFIC
				R9-6	YIELD TO PEDS	12	18	1.5							BOTT. OF SIGN 8 FT. ABOVE SURFACE
				R9-7	BIKES KEEP LEFT (SYMBOL)	12	18	1.5							FACING SB TRAFFIC
				R9-6	YIELD TO PEDS	12	18	1.5							FACING SB TRAFFIC. SIGNS INSTALLED FRONT AND BACK ON SAME POST
219	SS2	29+22	25-FT RT	R2-1	SPEED LIMIT 35	24	30	5	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	11	ST4	EXISTING SPEED LIMIT SIGN RELOCATED ON NEW POST
				W11-101	BIKES ON ROAD	30	18	3.75							BLACK ON YELLOW SIGN
221	SS2	10+50	22-FT LT	R1-1	STOP	30	30	6.25	IX	PERF SQ TUBE	2-IN X 12 GAGE	1	11	ST4	3M Diamond Grade DG3 Sheeting 4000 series with 3M 1160 Protective Sheeting
				D3-1	NE 94TH AVE X 2	30	9	3.75	IV						FACING WB TRAFFIC
				D3-1	NE 86TH ST X 2	30	9	3.75	IV						FACING WB TRAFFIC
222	SS2	34+20	25-FT RT	R9-3A	NO PED X-ING	18	18	2.25	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	8.5	ST4	SIGN FACING WEST
223	SS2	34+15	25-FT RT	R9-3A	NO PED X-ING	18	18	2.25	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	8.5	ST4	SIGN FACING WEST
224	SS3	38+05	25-FT RT	R2-1	SPEED LIMIT 35	24	30	5	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	11	ST4	FACING NB TRAFFIC
				W11-101	BIKES ON ROAD	30	18	3.75							FACING NB TRAFFIC
225	SS3	41+12	42-FT RT	R9-7	BIKES KEEP RIGHT (SYMBOL)	12	18	1.5	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	11	ST4	FACING NB TRAFFIC
				R9-6	YIELD TO PEDS	12	18	1.5							BOTT. OF SIGN 8 FT. ABOVE SURFACE
				R9-7	BIKES KEEP RIGHT (SYMBOL)	12	18	1.5							FACING SB TRAFFIC
				R9-6	YIELD TO PEDS	12	18	1.5							FACING SB TRAFFIC. SIGNS INSTALLED FRONT AND BACK ON SAME POST
226	SS5	62+36	25-FT RT	W3-5	SPEED LIMIT 25 AHEAD (SYMBOL)	36	36	9	IV	PERF SQ TUBE	2-IN X 12 GAGE	1	11.5	ST4	FACING NB TRAFFIC
227	SS5	65+18	28-FT RT	W14-1	DEAD END	30	30	6.25	IV	PERF SQ TUBE	2-IN X 12 GAGE	2	10	ST4	FACING NB TRAFFIC
228	SS5	65+5	35-FT LT	R1-1	STOP	30	30	6.25	IX	PERF SQ TUBE	2-IN X 12 GAGE	1	11.0	ST4	3M Diamond Grade DG3 Sheeting 4000 series with 3M 1160 Protective Sheeting

REV. NO.	DATE	BY	APPR

DWG:



Department of Public Works
CLARK COUNTY WASHINGTON
 proud past, promising future

SAMPLE SIGN INSTALL SPECIFICATIONS SHEET
 APPROVED

 COUNTY ENGINEER

07/17/19
 DATE

STANDARD
T2.20
 DETAIL
 DESIGNED
 DRAWN
 DATE