SEE STANDARD DETAIL F1 FOR CONSTRUCTION NOTES D1-D11. ALL NOTES APPLY UNLESS OTHERWISE NOTED. 5' MIN. WIDE SIDEWALK (SEE CONTRACT) SIDEWALK-BROOMED FINISH (TYP.) 2⁴, MIN. 40, MAX. EXPANSION JOINT SEE PLANS **SURFACE DETECTABLE** JOINT WARNING SURFACE . SEE STANDARD DETAIL F10 PEDESTRIAN CURB - (TYP.) (TYP.) -CL 4000 CONCRETE CONSTRUCTION JOINT **EXPANSION** JOINT CEMENT CONCRETE CURB & GUTTER (SEE NOTE R4) 1.5% OR FLATTER RECOMMENDED ISOMETRIC VIEW FOR DESIGN/FORMWORK (2% MAX) 7.5% OR FLATTER RECOMMENDED FOR DESIGN/FORMWORK (8.3% MAX) 1/2" MAX. SEE NOTE D10 5' MIN. (SEE PLANS) Z 15% MAX. 8" MIN. (SEE NOTE D1 AND D11) 6"x6" 10 GA WIRE MESH EXPANSION JOINT 3" MIN OF CSBC SEE NOTE D6 SEE NOTE D5 SECTION (REVISIONS REVISE GRADES NO. BY BK



Department of Public Works

CLARK COUNTY
WASHINGTON
proud past, promising future

COMMERCIAL CEMENT CONCRETE APPROACH -ATTACHED SIDEWALK

SIDEWALK F17a

01/26/16 DATE DETAIL
DESIGNED
DRAWN
DATE 01/26/16

STANDARD

ATTACHED SIDE

APPROVED

APPROVED